

SteriKLEEN[™] & SteriLUBE[™] Instructions for Use

SteriKLEEN™ ST-400622 Dental Handpiece Cleaner

For the removal of residual hydrocarbon oils, greases and other contaminants in previously <u>used</u> dental handpieces prior to the first use and application of SteriLUBE™ Dental Handpiece Lubricant. <u>New</u> handpiece components and bearings are typically coated with a hydrocarbon-based rust preventative oil as a preservative against corrosion during storage. This preservative coating must be removed from new handpieces using SteriKLEEN prior to the initial application of SteriLUBE.

- 1. Fit SteriKLEEN aerosol can with appropriate handpiece nozzle tip.
- 2. With handpiece head in downward position, spray into handpiece drive air line port for 2 seconds and spray until expelled fluid is clear.
- 3. With the head tilted downward while cupping with a paper towel, run the handpiece at normal speeds for 10-15 seconds purging excess cleaner, repeating until all debris is expelled.
- 4. Wipe down and dry handpiece completely before application of SteriLUBE Lubricant.
- 5. Periodic applications of SteriKLEEN are advisable when water flushing is not effective in removing patient debris prior to lubrication/sterilization between patients.

SteriLUBE™ ST-400621 Dental Handpiece Lubricant

High-Performance PFPE Lubricant offering "Superior Viscosity and Protection" against friction and wear when following CDC guidelines and used consistently between patients. SteriLUBE is a Non-Nutrient Food Grade Synthetic Lubricant with High-Temperature Stability, ideally suited for steam and RapidHeat™ High-Velocity Hot Air sterilizers.

- 1. Handpieces must be thoroughly purged of all previous lubricants and other contaminants using SteriKLEEN Handpiece Cleaner prior to application of SteriLUBE Handpiece Lubricant.
- 2. Apply 2-3 drops of SteriLUBE Dental Handpiece Lubricant into drive air line port.
- 3. Run handpiece at normal speeds to expel any excess lubricant with the head tilted downward, cupping with a paper towel.
- 4. Repeat application if expelled lubricant is discolored and not clear.
- 5. Wipe down handpiece and sterilize.

013120-1

CPAC logo, SteriKLEEN™, SteriLUBE™, and RapidHeat™ are trademarks of CPAC Equipment, Inc.